

NorthEast Monitoring, Inc. advancing Holter technology™

DR200/HE Holter and Event Recorder

Meets EC-38 standard + 14-day Holter capability + Ergonomic

Design

Proven reliability

Maximize Holter and Event reimbursements

 Reduce artifact with low-cost, shielded cables

> Pacemaker detection standard

Foreign language interface

✦
Industry-leading
3-year warranty



The DR200/HE is the industry's first combination14-day Holter plus Event recorder. It can be deployed to a patient in either Holter or Event mode. In Holter mode with a single, fully charged AA battery and a 1GigaByte data card, the unit can operate as a 14-day Holter. When the DR200/HE is combined with LX Analysis software, you have the flexibility to use your capital equipment in the most efficient manner and you've increased the probability

of capturing elusive cardiac events. It is the best solution for your practice and the best solution for your patient, which is another good combination!

The DR200/HE blends the features of the DR200/E "Tel-a-heart" Event recorder (see the DR200/E Data Sheet for complete details) and the established technology of the tried-and-true "workhorse" DR180+ Holter in a single, compact, rugged unit. New advanced DSP hardware and specially designed signal processing algorithms squeeze every milli-watt out of the battery to establish a new price-performance benchmark in ambulatory cardiac monitors. The unit is approximately one-half the size and weight of the DR180+, has smaller cable profiles for patient comfort, yet adds more functionality and convenience.

When deployed as a Holter, the DR200/HE has either 5- or 7-lead cables. When deployed as a Tel-a-heart Event monitor, it uses a 2-lead cable. The DR200/HE kit includes Holter and Event cables (including spares), pouch, belt clip, neck lanyard, removable media memory card, User's Manual and Hook-up Guide.

At NorthEast, we are advancing Holter technology - smaller in size, lower in cost, compatible with all levels of LX Analysis, the industry's best warranty of 3 years, with an optional extension to 5 or more years – the DR200/HE is the technology and quality leader in the industry today.

For more information on the DR200/HE combination Holter and Event Recorder, please contact NorthEast or read on for more details.

DR200/HE[™]Features

Meets EC-38 standard Meets applicable sections of ANSI/AAMI ED38-1994 "Ambulatory Electrocardiographs." 14 day Holter capability captures infrequent cardiac events Efficient low-power design and robust LX Analysis software now makes it possible to use the DR200/HE in Holter-mode over a 14-day period to capture infrequent cardiac events without the need to rely on patient interaction or automatic detection. Ergonomic design DR200/HE Specifications Large, easy view LCD (liquid crystal display) screen, soft-keys and a very simple user interface make the unit exceptionally easy to use. **Recording duration:** Proven reliability 14 days with alkaline battery Built on the platform of the reliable DR180+, there are thousands of Holter units deployed worldwide. Real-world experience is designed into every unit. **Recording bandwidth:** Maximize Holter and Event reimbursements 0.05 - 70 Hz Our system allows your office to "capture" reimbursement for all components of CPT (Current Procedural Terminology) allowed for Holter and Event. Removable digital storage memory (compact flash) allows for rapid **Resolution:** re-deployment of the unit to the next patient. 12-bit, 12.50 µV/LSB Reduce artifact with low cost, shielded cables Sampling rate: Shielded cables provide better signal integrity and noise immunity. Our cables are 180 samples/second carefully shielded and impedance matched and provide better SNR than any other cable on the market. Low cost cables drive down the total cost of ownership. Dimensions: 8.6 cm x 6.0 cm x 2.0 cm Pacemaker detection standard (3.9 in x 2.4 in x 0.8 in) The conflicting requirements for signal sensitivity (wide bandwidth and high sample rate) and long battery life have been uniquely resolved to provide the most accurate diagnostic information. Weight: 99.3 grams (3.5 oz), with battery Foreign language interfaces 70.9 (2.5 oz), without battery Multiple foreign languages are programmed into each unit to suit diverse patient populations. **Power:** Industry-leading 3-year warranty 1 AA battery: alkaline, NiMH rechargeable, These units are built-to-last. Our field return rate is proven to be so low that we can or lithium offer the industry's longest warranty -- and then extend that to 5 or more years to add even more value to your investment. Storage capacity: Maximize good quality recording cycles 32 MB - 1 GB Compact flash. Checks battery state and lead hook-up quality, date and Patient ID on LCD prior to deployment. No mix-ups with patient data because patient ID is encoded on memory card. Distributed by: All digital recording Reliable digital technology is used throughout, enhancing service life and lowering total cost of ownership. Compatible with NorthEast LX® Analysis software (See DR200/E Data Sheet for additional, event-specific features.) FDA K061293

NB: In the U.S.A., Federal Law restricts devices to sale by or on the order of a physician. For in vitro diagnostic use. Not intended to replace real-time telemetry monitoring for patients suspected of having life-threatening arrhythmias. January, 2007





Maynard, MA 01754 U.S.A.

www.nemon.com

phone: 978-461-3992 fax: 978-461-5991 toll free: 866-346-5837

